

### Luggage Capacity

Rear seats upright

Height 39.5 inches/1,002mm Width 44.3 inches/1,124mm

Loadspace volume 35.1 cu.ft./994 litres

(34.7 cu.ft./983 litres where reclining seat specified and reclined)

Loadspace width between arches 40.9 inches/1,040mm Length at floor 42.6 inches/1,082mm

Rear seats folded

Height 39.5 inches/1,002mm Width 44.3 inches/1,124mm

Loadspace volume 74.1 cu.ft./2,099 litres

Loadspace width between arches 40.9 inches/1,040mm Length at floor 60.2 inches/1,529mm

Maximum box size/length x width x height 49.8 x 40.3 x 32.1 inches/1,265 x 1,024 x 815mm

### Headroom

Maximum front headroom 39.3 inches/997mm (identical for sunroof or non-sunroof vehicles)

Rear headroom 38.4 inches/974mm



### Wading Depth

Maximum wading depth 27.6 inches/700mm with air suspension raised

## PERFORMANCE & WEIGHTS

WEIGHTS	V8 5.0L	V8 SUPERCHARGED 5.0L
Total/Base Curb Weight	5,697lb/2,584kg	5,891lb/2,672kg
Gross vehicle weight	7,055lb/3,200kg	7,055lb/3,200kg
Maximum payload	1,290lb/585kg	826-1,014lb/375-460kg
Maximum roof rack (including roof rack)	220lb/100kg	220lb/100kg

### TOWING (towing pack optional)

Unbraked trailer	1,650lb/750kg	1,650lb/750kg
Trailer with over-run brakes	7,700lb/3,500kg	7,700lb/3,500kg
Maximum coupling tongue weight	551lb/250kg	551lb/250kg

### PERFORMANCE

Maximum speed mph/kph	130/210	140/225
0-60mph	7.2	5.9
0-100kph	7.5	6.2

Usable fuel tank capacity 23 gallons (104.5 litres).

Low fuel warning at 2.1 gallons (8 litres) approximately.

### Dimensions & Capability

Thanks to its innovative cross-linked air suspension, the Range Rover can maintain a level ride height even over undulating terrain and be set to lower gently to ensure easy entry and exit when parked. Despite its impressive power and peerless capabilities, front and rear Park Distance Control and speed sensitive power-assisted rack and pinion steering ensure that manoeuvring in tight spots is always a simple, trouble-free operation. With up to 74.1 cubic feet/2,099 litres of cargo space the Range Rover again demonstrates its breadth of capability.

### Performance & Weights

The Range Rover Supercharged has an impressive 0-100kph time of 6.2 seconds. Both the fuel economy and the performance are aided by the use of aluminum components that include the hood assembly, outer door panels and inner door construction, wheels, transmission housing and front fenders.

## TECHNICAL SPECIFICATION

ENGINE DATA	V8	V8 SUPERCHARGED
Capacity	5.0 litres	5.0 litres
No. of cylinders	8	8
Cylinder layout	Longitudinal V8	Longitudinal V8
Bore inches/mm	3.6 inches/92.5mm	3.6 inches/92.5mm
Stroke inches/mm	3.7 inches/93mm	3.7 inches/93mm
Compression ratio (:1)	11.5 (+/- 0.5)	9.5 (+/- 0.5)
Cylinder head material	Aluminum	Aluminum
Cylinder block material	Aluminum	Aluminum
Ignition system	Denso pan PAG EMS Generation 1.6	Denso pan PAG EMS Generation 1.6
Valves per cylinder	4	4
Maximum power bhp @ rpm	375 @ 6,500	510 @ 6,000-6,500
Maximum torque lb-ft @ rpm (Nm @ rpm)	375 @ 3,500 (510 @ 3,500)	461 @ 2,500-5,500 (625 @ 2,500-5,500)

### TRANSMISSION DATA

Transmission type	Automatic	Automatic
Gear ratio 6th (High/Low) :1	0.691/2.020	0.691/2.020
5th (High/Low) :1	0.867/2.540	0.867/2.540
4th (High/Low) :1	1.143/3.350	1.143/3.350
3rd (High/Low) :1	1.521/4.460	1.521/4.460
2nd (High/Low) :1	2.340/6.860	2.340/6.860
1st (High/Low) :1	4.171/12.220	4.171/12.220
Reverse (High/Low) :1	3.403/9.960	3.403/9.960
Final Drive ratio :1	3.540	3.540
Transfer box ratio High :1	1	1
Transfer box ratio Low :1	2.93:1	2.93:1
Shift-on-the-move (mph/kph) - max High to Low	25/40	25/40
Low to High (mph/kph)	38/60	38/60
In gear speed (mph/kph) 6th High	130/210	140/225
1st High (mph/kph)	33/53	31/50
1st Low (mph/kph)	11/18	11/17

### BRAKES

Front Type	Twin 48mm piston sliding caliper/ventilated disc	6 piston fixed caliper/ventilated disc
Front size (inches/mm)	14.2 x 1.2/360 x 30	15 x 1.3/380 x 34
Rear Type	Single 45mm piston sliding caliper/ventilated disc	
Rear size (inches/mm)	13.9 x 0.8/354 x 20	14.4 x 0.8/365 x 20
Parking (electronically activated)	Duo Servo	Duo Servo

