Mechanical	s	PRO-4X	sv
Engine			
VQ40DE - 4.0-litre DOHC 24-valve V6 engine	s	s	s
Horsepower - 261 HP @ 5600 rpm	S	S	S
Torque - 281 lb-ft @ 4000 rpm	s	s	S
Emissions - LEV2 ULEV	S	S	S
Continuously Variable Valve Timing Control System (CVVTCS)	s	s	S
Variable Intake System	S	S	S
Nissan Direct Ignition System with platinum-tipped spark plugs	s	s	S
Electronic drive-by-wire throttle	S	S	S
Engine block heater Drivetrain	s	S	s
6-speed close-ratio manual transmission	s	s	
5-speed automatic transmission	0	AT	S
4-Wheel Drive system with switch-operated 2-speed transfer case	s	s	s
4-wheel Active Brake Limited Slip (ABLS)	S	S	S
Traction Control System (TCS)	s	s	s
Vehicle Dynamic Control (VDC)	S	S	S
Hill descent control and hill start assist (automatic transmission only)		AT	
Electronic locking rear differential		S	
Transmission cooler (automatic transmission only) Brakes	0	AT	S
4-wheel vented disc brakes	s	s	S
4-wheel Anti-lock Braking System (ABS) with G-sensor	S	S	S
Electronic Brake force Distribution (EBD) Suspension and Steering	s	s	S
Front: Independent double-wishbone	s	s	s
Rear: Multi-leaf with solid axle	S	S	S
Bilstein® off-road performance shock absorbers		s	
Front and rear stabilizer bars	S	S	S
Engine-speed-sensitive power-assisted rack-and-pinion steering Exterior Features	S	S	s

	S	PRO-4X	SV
Styling			
Tubular roof rack with covered gear box, crossbars and air dam	s	s	s
Roof-rack-mounted off-road lights		s	
Tubular step rails	s		s
Skid plates - oil pan, fuel tank, transfer case		s	
Rear bumper steps	S	s	s
Front tow hook	S	s	S
Black side mouldings		s	
Black outside mirrors and door handles	S	s	
Body-colour side mouldings			s
Body-colour outside mirrors and door handles			S
Fog lights		s	s
Sandblast aluminum front grille and lower front bumper	S	s	S
Dual power heated outside mirrors	s	s	s
UV-reducing solar glass	S	s	S
Rear privacy glass	s	s	s
Wheels and Tires			
16" x 7" 5-spoke aluminum-alloy wheels	s		
16" x 7" 6-spoke machined-finish aluminum-alloy wheels		s	
17" x 7.5" 8-spoke aluminum-alloy wheels			s
P265/70R16 BFGoodrich® Long Trail T/A® OWL tires	S		
P265/75R16 BFGoodrich® Rugged Trail T/A® OWL tires		s	
P265/65R17 BFGoodrich® Long Trail T/A® OWL tires			S
Full-size spare tire	s	s	s
Tire Pressure Monitoring System (TPMS)	S	S	S
Interior Features			
	S	PRO-4X	sv
Bluetooth® Hands-Free Phone System		s	s
Auto-dimming rearview mirror with compass		s	S
Air conditioning	s	s	s
			s
Trip computer with multiple functions			3

Power windows with driver's one-touch auto-down feature	S	S	s
Power door locks with auto-locking feature	s	s	s
Remote keyless entry	S	S	s
Cruise control	s	s	s
Retained accessory power and battery saver	S	S	s
Overhead sunglasses storage		S	s
Tilt steering column	S	S	s
Variable intermittent windshield wipers and rear wiper	s	S	s
Front map lights	S	S	s
Sunvisor extenders	s	s	s
Visor vanity mirrors (illuminated on SV)	S	S	s
Digital clock (in radio)	s	s	s
3 12-volt DC power outlets (2 "live")	S	S	s
4 cup holders and 2 bottle holders	s	s	s
Luggage side nets	S	S	s
Cargo net		s	s
Under-floor cargo area storage	S	S	s
Utili-track™ cargo channel system with 4 adjustable cleats	s	s	s
4 ceiling hooks and 2 cargo-area side hooks	S	S	s
First-aid kit		S	s
Seats up to 5	S	S	s
Seating Appointments			
	S	PRO-4X	SV
Cloth seating surfaces	s	s	s
8-way manual adjustable driver's seat with adjustable lumbar	S	S	s
Fold-flat front passenger's seat		s	s
Driver's seatback pocket		S	S
60/40 split fold-flat rear seats	s	s	s
Leather-wrapped steering wheel		S	S
Satin-chrome gauge trim			s
Easy Clean™ cargo area	S	s	s
Audio Systems			
	S	PRO-4X	SV
	I	I	I

AM/FM/CD audio system			s		
6 speakers			S		
380-watt Rockford Fosgate-powered audio system with AM/FM/in-dash 6-CD changer				s	s
9 high-performance speakers, including 8" subwoofer				S	s
Steering-wheel-mounted audio controls				s	s
MP3 and WMA audio playback capabilities				S	s
Auxiliary audio input jack				s	s
Speed-sensitive volume control				S	S
XM® Satellite Radio¹ (automatic transmission only)				AT	s
☐ Safety Features					
			S	PRO-4X	sv
Nissan Advanced Airbag System (AABS) with dual-stage supplemental front airbags with seat belt	and occupant-classific	ation sensors	s	s	s
Driver and front passenger seat-mounted side-impact supplemental airbags	•		S	S	S
Roof-mounted curtain supplemental side-impact airbags for outboard occupants side-impact protect	ction with rollover sense	or	s	s	s
3-point ALR/ELR passenger seat belt system (ELR for driver)			S	s	s
Front-seat active head restraints			s	s	s
Front seat belts with pre-tensioners and load limiters			S	S	s
LATCH System (Lower Anchors and Tethers for CHildren)			s	s	s
Energy-absorbing steering column			S	S	S
Zone Body construction with front and rear crumple zones			S	s	s
Hood-buckling creases			S	S	S
Pipe-style steel side-door guard beams			S	s	s
Immobilizer Key System			S	S	S
Anti-theft system			S	s	s
Curb Weights					
	S	PRO-4X		SV	
Base Curb Weights - kg (lbs) - Manual transmission	1982 (4369)	2004 (4417)			
Base Curb Weights - kg (lbs) - Automatic transmission	1989 (4385)	2011 (4432)	1	999 (4407)	
Fuel Economy	1				
	S	PRO-4X		sv	
Manual Transmission - L/100 km (mpg) - City	13.7 (21)	13.7 (21)			
Manual Transmission - L/100 km (mpg) - Hwy	10.5 (27)	10.5 (27)			
Automatic Transmission - L/100 km (mpg) - City	14.5 (19)	14.5 (19)	1	4.5 (19)	

Automatic Transmission - L/100 km (mpg) - Hwy	10.1 (28)	10.1 (28)	10.1 (28)
Capacities	•		•
	S	PRO-4X	SV
Interior Passenger Volume - L (cu. ft.)	2832 (100)	2832 (100)	2832 (100)
All seats in user positions - L (cu. ft.)	991 (35)	991 (35)	991 (35)
Second row folded flat	1869 (66)	1869 (66)	1869 (66)
Fuel Tank - L (Imp gal)	80 (17.6)	80 (17.6)	80 (17.6)
Towing capacity ² - kg (lbs)	2268 (5000)	2268 (5000)	2268 (5000)
Dimensions			
	S	PRO-4X	sv
Overall width - mm (inches)	1850 (72.8)	1850 (72.8)	1850 (72.8)
Overall height (with roof rack) - mm (inches)	1903 (74.9)	1903 (74.9)	1903 (74.9)
Overall length - mm (inches)	4540 (178.7)	4540 (178.7)	4540 (178.7)
Track width - mm (inches)	1570 (61.8)	1570 (61.8)	1570 (61.8)
Minimum ground clearance - mm (inches)	231-241 (9.1-9.5)	231-241 (9.1-9.5)	231-241 (9.1-9.5)
Wheelbase - mm (inches)	2700 (106.3)	2700 (106.3)	2700 (106.3)
Head room (front) - mm (inches)	1012 (39.9)	1012 (39.9)	1012 (39.9)
Head room (rear) - mm (inches)	998 (39.3)	998 (39.3)	998 (39.3)
Leg room (front) - mm (inches)	1077 (42.4)	1077 (42.4)	1077 (42.4)
Leg room (rear) - mm (inches)	874 (34.4)	874 (34.4)	874 (34.4)
Hip room (front) - mm (inches)	1420 (55.9)	1420 (55.9)	1420 (55.9)
Hip room (rear) - mm (inches)	1171 (46.1)	1171 (46.1)	1171 (46.1)
Shoulder room (front) - mm (inches)	1481 (58.3)	1481 (58.3)	1481 (58.3)
Shoulder room (rear) - mm (inches)	1481 (58.3)	1481 (58.3)	1481 (58.3)

Legend

AT Part of PRO-4X Automatic Transmission Package
 Optional
 Standard